

# TECHNICAL INFORMATION

## SPECIAL FEATURES

- ✓ very low density
- ✓ very low consumption
- ✓ for universal use
- ✓ integrated vapor barrier
- ✓ very good thread formation
- ✓ no danger of migration of any component
- ✓ shear-resistant wood flooring adhesive
- ✓ no adverse interaction with AKZENT parquet sealings, varnishes flow asphalt or old substrates
- ✓ extremely easy to spread

## SUITABLE SUBFLOORS

- ✓ sanded mastic asphalt screed
- ✓ concrete C 25 / 30 according to DIN 1045 (non-skid surface)
- ✓ calcium sulphate (flow) floors
- ✓ wooden planks, wood fibre boards
- ✓ STAUF levelling compounds for wood flooring
- ✓ Chipboards (P4 to P7)
- ✓ OSB boards (OSB/2 to OSB/4)
- ✓ Cement floors
- ✓ cement floors, concrete floors with residual moisture

## COLOUR

- ✓ milky transparent

## REQUIRED QUANTITIES PER M<sup>2</sup>

- ✓ approx. 550-1.600 g

## OPEN TIME

- ✓ approx. 30 min. at 20 °C

## ACCESSIBILITY

- ✓ after 12–24 hours

## SHELF LIFE

- ✓ 9 months

## AVAILABLE PACKAGING

- ✓ 11 kg recycle plastic bucket

## EMICODE

- ✓ EC 1<sup>PLUS</sup>

## GISCODE

- ✓ RS 10 solvent free



# CONTACT US TODAY

+492739301-0

info@stauf.de

www.stauf.de

STAUF KLEBSTOFFWERK GMBH

Oberhausener Str. 1 . 57234 Wilnsdorf . Germany

2205



# SPU 510

Wider range,  
less weight



# INCREASED COVERAGE

**EFFICIENT** With its particularly low density and very low consumption, STAUF SPU 510 sets new standards for parquet adhesives and continues STAUF's 20-year silane success story.

With STAUF SPU 510, significantly more square metres of parquet can be laid per kilogram of adhesive – **about 70% more!** This top product from the silane range of adhesives convinces with its outstanding technical properties and application approvals.

As part of the new ProForce product line, the SPU parquet adhesive is **an all-rounder** for all types of parquet and can be laid on any suitable parquet subfloor without the need for priming. It is also especially good at keeping large format boards (10:1 and wider) in shape. It is also possible to bond it directly to cement screeds with up to 4 CM% as a vapour barrier.

# LOWER WEIGHT

**LIGHT** A bucket of STAUF SPU 510 weighs only 11 kg. This filler-free adhesive is significantly lighter than comparable products – and is much more efficient in terms of consumption. Its **around 40%** lower consumption compared to conventional parquet adhesives not only saves resources but also reduces transport costs and benefits the installer.

# SUSTAINABLE PACKAGING

**CO<sub>2</sub>-REDUCED** Only buckets made from 100% recycled plastic are used for the new ProForce series. **This saves 36% CO<sub>2</sub> per bucket.** With its plastic handle, the container can be 100% recycled after use and returned to the recycling loop.



- Solvent-free – GISCODE RS 10
- Very low emissions
- no danger of migration of any component
- Isocyanate-free – particularly user-friendly



- 36% CO<sub>2</sub> saving
- New recyclable plastic handle
- Bucket made of recycled material



14.6 m<sup>2</sup>

— 11 KG —



8.46 m<sup>2</sup>



**goes about 70% further!\***

**More ProForce products**

\*Consumption using STAUF notched trowel 4: 0.75kg/m<sup>2</sup> and for XYZ consumption using STAUF notched trowel 4: 1.3kg/m<sup>2</sup>