

# TECHNICAL INFORMATION

# CONTACT US TODAY

⊠ info@stauf.de

www.stauf.de

#### SPECIAL FEATURES

- ✓ High shear strength
- ✓ Excellent ridges
- ✓ Suitable for use with floor heating systems
- ✓ Elastic adhesive (EN 14293 + ISO 17178)
- ✓ Coloured version for dark timber types available
- Solvent-free, no labelling required and isocyanatefree (especially userfriendly)

#### SUITABLE SUBFLOORS

- ✓ Sanded mastic asphalt
- Concrete (structured surface)
- Calcium sulphate (floating) screed
- ✓ Wood subfloors
- ✓ STAUF fillers
- Chipboard and OSB panels
- ✓ Cement screed

#### COLOUR

✓ Beige

#### REQUIRED QUANTITIES PER M2

✓ Approx.1,100 – 1,350 g

#### OPEN TIME

✓ Approx. 45 min. at 20°C

#### ACCESSIBILITY

✓ After approx. 48 hours

#### AVAILABLE PACKAGES

- ✓ 8 kg plastic bucket
- ✓ 18 kg plastic bucket

#### **EMICODE**

✓ EC1 RPLUS



#### STAUF KLEBSTOFFWERK GMBH

Oberhausener Str. 1. 57234 Wilnsdorf. Germany



# **SPU 460**

The all-rounder among parquet adhesives



# **MULTI-TALENT**

**MUST-HAVE** Everybody should have an all-rounder like this to hand: SPU 460 can be safely and easily applied to just about any type of parquet flooring. From ready-to-lay parquet flooring to solid floorboards up to 10:1 – this adhesive covers almost every conceivable application.

## **PLEASANT**

**EFFORTLESS** SPU 460 makes it easy for you: It cures fast and sets quickly. Its high shear strength, hard elastic deformability, excellent ridges and outstanding spreadability are further positive characteristics. Adhesive residue can be easily removed.

### **HARMLESS**

**USER-FRIENDLY** Awarded the highest possible EMICODE class EC 1 RPLUS, SPU 460 ensures a pleasant and healthy living environment: Our all-rounder is very low in emissions and at the same time solvent-free, requires no labelling and is isocyanate-free.

